

INTERNATIONAL CARTRIDGE CORPORATION

2273 Route 310
 Reynoldsville, PA 15851

Phone: 814-938-6820

Website: www.iccammo.com

| Cartridge Designation | Caliber(s) | Grain(s) | % lead content by weight | Unique Identifying Characteristics |
|-----------------------|------------|----------|--------------------------|---|
| 223 Remington** | 223 | 55 | <1% | Copper jacket, compressed powder core, open tip |
| 243 Winchester | 243 | 85 | <1% | Barnes TTSX Projectile; solid copper, polymer tip |
| 270 Winchester | 277 | 130 | <1% | Barnes TTSX Projectile; solid copper, polymer tip |
| 308 Winchester | 308 | 150 | <1% | Barnes TSX Projectile; solid copper, open tip |
| 308 Winchester | 308 | 150 | <1% | Barnes TTSX Projectile; solid copper, polymer tip |
| 30-06 Springfield | 308 | 150 | <1% | Barnes TSX Projectile; solid copper, open tip |
| 30-06 Springfield | 308 | 180 | <1% | Barnes TTSX Projectile; solid copper, polymer tip |
| 7 mm Remington Mag. | 284 | 140 | <1% | Barnes TTSX Projectile; solid copper, polymer tip |
| 7 mm-08 Remington | 284 | 140 | <1% | Barnes TTSX Projectile; solid copper, polymer tip |
| 300 Winchester Mag. | 308 | 180 | <1% | Barnes TTSX Projectile; solid copper, polymer tip |

** Frangible bullets are certified for use on appropriate non-game species only.